

Mainboard Comparison Chart

Updated: 11-30-2000



Model	CPU Type	Form Factor	Chipset Type	FSB Speed	EIDE	Built-in Sound	Built-in Video	Max RAM	AGP Slot	PCI Slots	ISA Slots	CNR Slot	AMR Slot
K7KX-A	Slot A*	ATX	VIA KX133	200Mhz	Ultra/66	Yes	No	3 DIMM 768MB	4X	5	1	No	Yes
S3Pro-AU+	Socket 370**	ATX	VIA Apollo 133A	133Mhz	Ultra/100	Yes	No	3 DIMM 768MB	4X	5	1	No	Yes
S3Pro-AU	Socket 370**	ATX	VIA Apollo 133A	133Mhz	Ultra/66	Yes	No	3 DIMM 768MB	4X	5	1	No	Yes
S3Pro-MU	Socket 370**	Micro ATX	VIA Apollo 133A	133Mhz	Ultra/66	Yes	No	3 DIMM 768MB	4X	2	1	No	Yes
S3Pro-M	Socket 370**	Micro ATX	VIA Apollo 133A	133Mhz	Ultra/66	Yes	No	3 DIMM 768MB	2X	2	1	No	Yes
S3815-A	Socket 370**	ATX	Intel i815	133Mhz	Ultra/66	Yes	Yes	3 DIMM 512MB	4X	5	0	No	Yes
S3815-AE	Socket 370**	ATX	Intel i815E	133Mhz	Ultra/100	Yes	Yes	3 DIMM 512MB	4X	6	0	Yes	No
S3815-ANE	Socket 370**	ATX	Intel i815E w/ Ethernet	133Mhz	Ultra/100	Yes	Yes	3 DIMM 512MB	4X	6	0	Yes	No
S381-M+	Socket 370**	Micro ATX	Intel i810 DC-100 4MB VRAM	100Mhz	Ultra/66	Yes	Yes	2 DIMM 512MB	No	3	0	No	Yes
S381-M	Socket 370**	Micro ATX	Intel i810	100Mhz	Ultra/66	Yes	Yes	2 DIMM 512MB	No	3	0	No	Yes
S381-F	Socket 370**	Flex ATX	Intel i810	100Mhz	Ultra/66	Yes	Yes	2 DIMM 512MB	No	2	0	No	Yes
S381-FN	Socket 370**	Flex ATX	Intel i810 w/RTL Ethernet	100Mhz	Ultra/66	Yes	Yes	2 DIMM 512MB	No	2	0	No	Yes
S381-FNE	Socket 370**	Flex ATX	Intel i810E w/RTL Ethernet	133Mhz	Ultra/66	Yes	Yes	2 DIMM 512MB	No	2	0	No	Yes
S3PM-F	Socket 370**	Flex ATX	VIA Apollo PM601	133Mhz	Ultra/66	Yes	Yes	2 DIMM 512MB	No	2	0	No	Yes
S3PM-FN	Socket 370**	Flex ATX	VIA Apollo PM601 w/RTL Ethernet	133Mhz	Ultra/66	Yes	Yes	2 DIMM 512MB	No	2	0	No	Yes

*Slot A CPUs: Supports all available AMD Athon CPUs up to 1GHz.

**Socket 370 CPUs: Supports all available Intel Pentium III & Celeron Socket 370 CPUs up to 1GHz. Models S381-M/M+, require V2.01 for FC-PGA support.

Specifications subject to change without notice. All registered trademarks are the property of their respective owners.